



hp workstations c3700 and c3750

data sheet



design power

Pure processing power. The HP Workstations c3700 and c3750 are ultimate uni-processor RISC-based UNIX workstation with a single PA-8700 750-MHz or PA-8700+ 875-MHz processor delivering leadership 3D graphics performance, expandability and value. Engineers and scientists working in the automotive, aerospace, and EDA markets will particularly appreciate the compute power to help slash product cycle times and shorten time to market. Team the power of the PA-RISC processor with the capacity to support up to 8-GB RAM, 146-GB internal disk, and six PCI cards, and you have a workstation that breaks through traditional bottle-necks of computation and desktop 3D design.



3D graphics performance, expandability and value

features

750-MHz PA-8700 or
875-MHz PA-8700+ processor

2.25-MB on-chip cache

four-way set associative cache

8-GB SDRAM capacity

hp fxe graphics card

hp fx⁵ pro graphics card

hp fx¹⁰ pro graphics card

hp Fire GL-UX graphics card

rack mountable

expansive tower with 6 industry-
standard PCI slots

binary compatibility with future
PA-RISC and Intel® Itanium®
processors

benefits

delivers application performance to complete your designs
faster

minimizes system latency with large on-chip cache,
enhances system performance with greater application
speed and throughput

decreases the miss rate of direct mapped cache –
requiring less disk-to-cache access for instructions and
data, providing higher performance

delivers the largest RAM capacity available on any uni-
processor workstation for higher application performance
with less disk access, supports interactive work with
complex 3D designs and digital prototypes

provides full-featured, 3D capability for universal access to
all types of data across diverse, cross-functional teams

delivers mid-range 3D graphics performance for
mechanical design work with faster visualization of mid-
size assemblies

delivers high-end 3D graphics performance for mechanical
design and analysis for greater user productivity and
performance

delivers fastest 3D UNIX graphics performance for
mechanical design and analysis with greatest user
productivity and performance

supports on-side configuration as well as upright, desktop
placement for space optimization when deployed in your
computer rooms

provides more capacity for PCI I/O cards for flexibility to
expand your system

ensures smooth transition to hp's next-generation high-
performance systems, protects your investment in
applications, data and systems

hp workstation c3700 and c3750 technical specifications

processor	hp c3700	hp c3750
type	PA-8700	PA-8700+
clock frequency	750-MHz	875-MHz
number of processors	1	1
cache (on-chip)		
total cache	2.25-MB	
instruction	0.75-MB	
data	1.50-MB	
main memory		
bus bandwidth	1.9-GB/s	
RAM type	120-MHz SDRAM	
capacity	512-MB to 8-GB	
memory slots	8 DIMMs	
storage bays	1 floppy, 1 optical, 2 Ultra 2 SCSI LVD	
internal storage (2 bays)	up to 2 devices, 146-GB maximum Ultra 2 SCSI LVD, 80 pin SCA connector 18-GB (10K RPM) 36-GB (10K RPM) 73-GB (10K RPM) 36-GB (15K RPM)	
external storage		
NSE SCSI (HD50)	1 port - up to 7 devices	
Ultra2 SCSI LVD	1 port - up to 13 devices	
removable media		
floppy drive	1 floppy drive (3.5 inch/1.44-MB)	
optical drive	1 DVD or CD-RW	
expansion slots (6 total)		
PCI 1X (half card)	2 slots	
PCI 2X (full size)	3 slots	
PCI 4X (full size)	1 slot	
integrated networking		
LAN data rate	10/100-Mb/s	
built-in I/O		
serial interface 9-pin DIN	2 ports	
parallel interface 25-pin DIN	1 port	
USB (Universal Serial Bus) Series A	2 ports (keyboard and mouse only)	
audio		
type	integrated, CD-quality stereo	
inputs	stereo line-in, MIC-in	
outputs	stereo line-out, internal speaker, headphones	
environmental specifications		
altitude		
- operating	0-3000 m (0-10,000 ft)	
- non-operating	0-4500 m (0-15,000 ft)	
temperature		
- operating	5 to +40 degrees C	
- non-operating	-40 to +70 degrees C	
humidity		
- operating	15 to 80% (non condensing)	
vibration		
- operating random	0.21 G rms, 5-500-Hz	
- swept sine survival	0.5 G peak, 5-500-Hz	
- random survival	2.09 G rms, 5-500-Hz	
safety	UL1950, CUL to CSA C22.2#950, and TUV GS, Mark to EN60950/IEC950	

physical dimensions

height
width
depth

height
width
depth

rack orientation

net weight

minimum configuration
fully loaded

power requirements

input current

line frequency

maximum power input

supported operating systems

hp-ux 11i TCOE (Technical Computing Operating Environment)

hp-ux 11i MTOE (Minimal Technical Operating Environment)

hp-ux 11.0

monitors

hp L2025

hp L1325

hp wide-aspect

hp p1130

hp p920

leadership graphics—entry 3D

hp *fxe*

leadership graphics—mid-range 3D

hp *fx⁵ pro*

leadership graphics—high-end 3D

hp *fx¹⁰ pro*

leadership graphics—extreme 3D

hp Fire GL-UX

deskside configuration

44.5 cm (17.5 inches)

22.9 cm (9.0 inches)

49.5 cm (19.5 inches)

racked configuration

6 EIA units

48.3 cm (19 inches)

66.5 cm (25.8 inches)

system racks on its side

20.9 kg (45.9 lbs.)

25.4 kg (55.8 lbs.)

7.4 amps RMS max @ 100-120 V

3.8 amps RMS max @ 220-240 V

50-60-Hz

805 watts @120 VAC, 60-Hz

20 inch LCD, flat-panel

18 inch LCD, flat-panel

24 inch CRT, flat-screen, wide aspect

21 inch CRT, flat-screen

19 inch CRT, flat-screen

4 maximum, 24-MB FB memory,
9.5-MB maximum texture memory at
1280 x 1024 resolution

1 maximum, 64-MB FB memory,
48-MB maximum texture memory at
1280 x 1024 resolution

1 maximum, 128-MB FB memory,
110-MB maximum texture memory at
1280 x 1024 resolution

1 maximum, 128-MB FB memory,
110-MB maximum texture memory at
1280 x 1024 resolution

For more information about the HP leadership graphics program:

www.hp.com/go/leadershipgraphics

Screen image courtesy of EDS PLM Solutions and Ducati Motor Holding S.p.A., and EDS PLM Solutions and Industrial Juguetera, S.A. (INJUSA). UNIX is a registered trademark of The Open Group in the United States and other countries. All other product names mentioned herein may be trademarks of their respective companies.

Information in the document is subject to change without notice.

© 2002 Hewlett-Packard Company

11/18/02

5981-3990EN